

AIR LIFTING BAGS

Only require 25 mm clearance to lift up 67,700 kg. Will run off most workshop air supplies (requires 120 psi), great for lifting on soft surfaces.



Code	Max Lifting Power (kg @ 8 bar)	Min. Height (mm)	Max. Height (mm)	Dimensions (mm)	Weight (kg)	1 Day Rate (\$)*	After 4 Days (\$)*	After 8 Days (\$)*
V24 (bag only)	24,000	25	306	520 x 620	7.3	85.00* (60.00)	68.00* (48.00)	51.00* (36.00)
V68 (bag only)	67,700	25	520	950 x 950	21.9	120.00* (90.00)	96.00* (90.00)	72.00* (54.00)

*Complete with deadman controller (can operate 2 air bags) and 1 x 10 metre hose

Code	Description	Weight (kg)	1 Day Rate (\$)*	After 4 Days (\$)*	After 8 Days (\$)*
VRAB	Remote Air Bottle	6.6	45.00	36.00	27.00
VABCO	Air Bag Controller	2.0	25.00	20.00	15.00
VABH	Air Hoses	2.0	5.00	4.00	3.00

Air bottle refills \$15.00*

RATCHET JACKS

Ratchet and self contained hydraulic toe jacks

Ratchet and self contained hydraulic jacks are a safe and easy to use lifting system with very low toe height, they easily fit into areas where conventional lifting systems will not.



Code	Tonnes	Ratchet/Hydraulic	Min. Toe Height (mm)	Stroke (mm)	Jack Closed Height (mm)	Weight (kg)	1 Day Rate (\$)*	After 4 Days (\$)*	After 8 Days (\$)*
85A	5	Ratchet	44	254	432	13.6	30.00	24.00	18.00
86A	5	Ratchet	44	330	508	15.9	30.00	24.00	18.00
JA1220	8	Hydraulic	67	305	439	22.2	35.00	28.00	21.00
JA1230	12	Hydraulic	67	305	451	31.0	45.00	36.00	27.00
JA1260	24	Hydraulic	73	305	500	64.7	70.00	56.00	42.00

Hydraulic Toe Jack Sets

Hydraulic Toe Jacks are a safe and efficient alternative to mechanical or ratchet jacks. The advantage with hydraulic toe jacks is you can operate more than one lifting point from the one pump, giving the operator more control for lifting / lowering. Very low minimal height.

Code	Tonnes	Stroke (mm)	Min. Toe Height (mm)	Weight (kg)	1 Day Rate (\$)*	After 4 Days (\$)*	After 8 Days (\$)*
S1-120T*	5	120	32	6.6	30.00	24.00	18.00
S1-150T*	5	150	32	6.9	30.00	24.00	18.00
S1-300T*	5	300	32	9.6	30.00	24.00	18.00

*Kits include: Cylinder, toe, and base attachments (R-107 & R-306).

TOE JACK HAND PUMPS

Hand operated 2 speed pumps

Special Hand Pump for Hydraulic Toe Jacks!

Code	Usable Oil (cc's)	Valve Type	Pressure	Weight (kg)	1 Day Rate (\$)*	After 4 Days (\$)*	After 8 Days (\$)*
P1B-5000	600	Single acting	350 bar	7.0	22.50	18.00	13.50

To ensure correct operation and to maintain safety standards, HTC Hydraulic Toe Jacks must be powered by special P1B-5000 Hand Operated Pump.

www.specialisedtools.co.nz

*Rates are GST exclusive and do not include damage waiver.
Discounts on long term hires available.

